

# Urochem 306

## EPOXY ENAMEL PAINT

### DESCRIPTION

**Urochem 306** is a high gloss twin pack epoxy enamel paint which provides a tough chemical resistant easily cleaned surface, which once cured, is non-toxic.

### PRODUCT APPLICATION

- **Urochem 306** is used as a surface coating for floors, concrete surfaces, machinery, pipes, ablution blocks, hospitals, schools etc.
- The product should be applied by experienced personnel only.

### SURFACE PREPARATION

- All surfaces to be clean, sound, and dry and free of loose material. Remove dust, laitance, and oils from the substrate before coating commences.
- Prime if required to achieve a smooth finish.

### APPLICATION

The product is mixed as supplied with a low-speed mixer and a flat paddle until streak free and homogeneous. The product is then poured into paint trays and applied by roller or brush.

### CLEANING

Clean all tools and equipment immediately after use with **Urochem 901** as the cured material is very difficult to remove.

### SAFETY

Contains organic solvents. Flammable. Do not use in confined spaces. Ensure adequate ventilation and the absence of any ignition source. Contact with the skin should be avoided by wearing gloves, eye protection and protective clothing. In case of eye contact wash well and obtain medical advice. Use only in well ventilated areas.



### Urochem Trading (Pty) Ltd

Unit XP2, AEL Industrial complex, Cnr Ecqip and Weighbridge  
Modderfontein, Gauteng; 1645

(+27) 11 608 2073 • [www.urochem.co.za](http://www.urochem.co.za)

## Urochem 306

### EPOXY ENAMEL PAINT

#### TYPICAL PROPERTIES

<b>Mixing Ratio</b>	Mix as supplied - Do NOT split kit
<b>Pot Life</b>	5 Hours @ 25° C
<b>Practical Cure</b>	24Hours
<b>Full Cure</b>	7 Days
<b>Chemical Resistance</b>	Dilute acids, dilute alkalis and general chemicals
<b>Colour</b>	Amber or pigmented as per order
<b>Density</b>	1,3 (cured)
<b>Theoretical Coverage</b>	4 - 8m <sup>2</sup> / Lt / coat - 2 coats min
<b>Shelf Life</b>	12 Months
<b>Application Temp.</b>	5 - 35°C
<b>Service Temp.</b>	50° C Wet / 80° C Dry
<b>Pack Size</b>	2 Lt & 5 Lt Kits
<b>Cleaning</b>	<b>Urochem 901</b>
<b>Storage</b>	Store in a cool dry place

The information supplied is believed to be reliable. As we do not have any control over the processing or application of the product, we cannot guarantee the results to be obtained. Users assume all risks and liability resulting from the use of this product and must confirm the suitability thereof by conducting their own tests. No guarantee is expressed or implied. Liability is limited to replacement of faulty material. Field service provided does not constitute supervisory responsibility.

#### FOR PROFESSIONAL USE ONLY



#### Urochem Trading (Pty) Ltd

Unit XP2, AEL Industrial complex, Cnr Ecqip and Weighbridge  
Modderfontein, Gauteng; 1645

(+27) 11 608 2073 • [www.urochem.co.za](http://www.urochem.co.za)